# **NECTRA LITE 14W 1330LM IP44**

**DETAILED CARD** 





#### **TECHNICAL PARAMETERS**

| Index:                   | 502606  |
|--------------------------|---------|
| Ingress protection:      | IP44/20 |
| Nominal power [W]:       | 14      |
| Luminous flux [lm]*:     | 1330    |
| Colour temperature [K]:  | 4000    |
| Colour rendering index:  | >80     |
| Energy efficiency class: | E       |
| Material of the body:    | PC      |
| Colour of the body:      | white   |
| Diffuser type:           | OPAL    |
|                          |         |

#### **CHARACTERISTICS**

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

### **APPLICATION**

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



# **NECTRA LITE 14W 1330LM IP44**


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

| Nominal power [W]:                | 14      |
|-----------------------------------|---------|
| Colour temperature [K]:           | 4000    |
| Rated power of the luminaire [W]: | 14      |
| Luminous flux [lm]:               | 1330    |
| Diffuser type:                    | OPAL    |
| Luminous efficacy [lm/W]:         | 95      |
| Dimensions (H/W/T/S) [mm]:        | 145/66  |
| Energy efficiency class:          | Е       |
| Ingress protection:               | IP44/20 |
| Electrical protection class:      | II      |
| Colour rendering index:           | >80     |
| Material of the body:             | PC      |
| Colour of the body:               | white   |
| Mounting dimensions [mm]:         | 120x130 |

| Working temperature [°C]: | from -20 to +40   |
|---------------------------|---|
| Index:                    | 502606  |
| EAN:                      | 5905963502606   |
| Category type:            | downlights  |
| Category of application:  | HoReCa, commercial facilities, educational institutions |
| LED lifespan L70B50 [h]:  | 30000   |
| LED lifespan L80B20 [h]:  | 20000   |
| Mounting version:         | recessed  |
| Photobiological safety:   | RG0 - exempt (no photobiological hazard)                |
| Warranty [years]:         | 5   |
| CE certificate:           | 346/2023  |
| Manual:                   | Download PDF  |
| Plik LDT:                 | Download  |

## **LIGHT CURVES**



Card creation date: 25 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

