

NECTRA LITE 17W 1650LM IP44

DETAILED CARD



TECHNICAL PARAMETERS

Index:	502613
Ingress protection:	IP44/20
Nominal power [W]:	17
Luminous flux [lm]*:	1650
Colour temperature [K]:	4000
Colour rendering index:	80
Energy efficiency class:	E
Material of the body:	PC
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LITE 17W 1650LM IP44

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	17	Working temperature [°C]:	from -20 to +40
Rated power of the luminaire [W]:	17	Index:	502613
Luminous flux [lm]:	1650	EAN:	5905963502613
Luminous efficacy [lm/W]:	97	Category type:	downlights
Energy efficiency class:	E	Category of application:	educational institutions, HoReCa, commercial facilities
Electrical protection class:	II	LED lifespan L70B50 [h]:	30000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	20000
Colour rendering index:	80	Mounting version:	recessed
Diffuser type:	OPAL	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Material of the body:	PC	Warranty [years]:	5
Colour of the body:	white	CE certificate:	346/2023
Dimensions (H/W/T/S) [mm]:	174/69	Manual:	Download PDF
Mounting dimensions [mm]:	145x155	Plik LDT:	Download
Ingress protection:	IP44/20		

LIGHT CURVES

