NECTRA LITE 20W 2000LM IP44

DETAILED CARD





Index:	502620
Ingress protection:	IP44/20
Nominal power [W]:	20
Luminous flux [lm]*:	2000
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Energy efficiency class:	Е
Material of the body:	PC
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LITE 20W 2000LM IP44

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20
Rated power of the luminaire [W]:	20
Luminous flux [lm]:	2000
Luminous efficacy [lm/W]:	100
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Diffuser type:	OPAL
Material of the body:	PC
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	224/84
Mounting dimensions [mm]:	195x210
Ingress protection:	IP44/20

Working temperature [°C]:	from -20 to +40
Index:	502620
EAN:	5905963502620
Category type:	downlights
Category of application:	educational institutions, HoReCa, commercial facilities
LED lifespan L70B50 [h]:	30000
LED lifespan L80B20 [h]:	20000
Mounting version:	recessed
Power factor:	0.91
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	<u>346/2023</u>
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 25 February 2025



