

NECTRA LITE 20W 2000LM IP44

DETAILED CARD



TECHNICAL PARAMETERS

Index:	502620
Ingress protection:	IP44/20
Nominal power [W]:	20
Luminous flux [lm]*:	2000
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	PC
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LITE 20W 2000LM IP44

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Working temperature [°C]:	from -20 to +40
Colour temperature [K]:	4000	Index:	502620
Rated power of the luminaire [W]:	20	EAN:	5905963502620
Luminous flux [lm]:	2000	Category type:	downlights
Diffuser type:	OPAL	Category of application:	HoReCa, commercial facilities, educational institutions
Luminous efficacy [lm/W]:	100	LED lifespan L70B50 [h]:	30000
Dimensions (H/W/T/S) [mm]:	224/84	LED lifespan L80B20 [h]:	20000
Energy efficiency class:	E	Mounting version:	recessed
Ingress protection:	IP44/20	Power factor:	0.91
Electrical protection class:	II	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Colour rendering index:	>80	Warranty [years]:	5
Material of the body:	PC	CE certificate:	346/2023
Colour of the body:	white	Manual:	Download PDF
Mounting dimensions [mm]:	195x210	Plik LDT:	Download