NECTRA LITE 20W 2000LM IP44

DETAILED CARD





Index:	502620
Ingress protection:	IP44/20
Nominal power [W]:	20
Luminous flux [lm]*:	2000
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	PC
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LITE 20W 2000LM IP44


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20
Colour temperature [K]:	4000
Rated power of the luminaire [W]:	20
Luminous flux [lm]:	2000
Diffuser type:	OPAL
Luminous efficacy [lm/W]:	100
Dimensions (H/W/T/S) [mm]:	224/84
Energy efficiency class:	Е
Ingress protection:	IP44/20
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	PC
Colour of the body:	white
Mounting dimensions [mm]:	195x210

Working temperature [°C]:	from -20 to +40
Index:	502620
EAN:	5905963502620
Category type:	downlights
Category of application:	HoReCa, commercial facilities, educational institutions
LED lifespan L70B50 [h]:	30000
LED lifespan L80B20 [h]:	20000
Mounting version:	recessed
Power factor:	0.91
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	<u>346/2023</u>
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES



Card creation date: 25 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



Certificate CE - Nr: 346/2023