NECTRA LITE 25W 2450LM IP44

DETAILED CARD





TECHNICAL PARAMETERS

Index:	502637
Ingress protection:	IP44/20
Nominal power [W]:	25
Luminous flux [Im]*:	2450
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	PC
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LITE 25W 2450LM IP44

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	25
Rated power of the luminaire [W]:	25
Luminous flux [lm]:	2450
Luminous efficacy [lm/W]:	98
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	>80
Diffuser type:	OPAL
Material of the body:	PC
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	224/84
Mounting dimensions [mm]:	195x210
Ingress protection:	IP44/20

Working temperature [°C]:	from -20 to +40
Index:	502637
EAN:	5905963502637
Category type:	downlights
Category of application:	HoReCa, commercial facilities, educational institutions
LED lifespan L70B50 [h]:	30000
LED lifespan L80B20 [h]:	20000
Mounting version:	recessed
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	346/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 25 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

