

NECTRA LITE 25W 2450LM IP44

DETAILED CARD



TECHNICAL PARAMETERS

Index:	502637
Ingress protection:	IP44/20
Nominal power [W]:	25
Luminous flux [lm]*:	2450
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	PC
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LITE 25W 2450LM IP44

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	25	Mounting dimensions [mm]:	195x210
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +40
Rated power of the luminaire [W]:	25	Index:	502637
Luminous flux [lm]:	2450	EAN:	5905963502637
Diffuser type:	OPAL	Category type:	downlights
Luminous efficacy [lm/W]:	98	Category of application:	HoReCa, commercial facilities, educational institutions
Dimensions (H/W/T/S) [mm]:	224/84	Warranty [years]:	5
Energy efficiency class:	E	LED lifespan L70B50 [h]:	30000
Ingress protection:	IP44/20	LED lifespan L80B20 [h]:	20000
Electrical protection class:	II	Mounting version:	recessed
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PC	Manual:	Download PDF
Colour of the body:	white	Plik LDT:	Pobierz

Card creation date: 23 April 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 346/2023