

# TYTAN LED ENDURA MINUS 1150MM 9000LM IP66 840 (56W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	358043
Ingress protection:	IP66
Impact resistance:	IK09
Nominal power [W]:	56
Luminous flux [lm]*:	9000
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Material of the body:	PC
Diffuser material:	PC

## CHARACTERISTICS

TYTAN LED is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded led diodes and new LED modules have influence on a very high luminous flux: 150 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED modul is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/- 40mm. Standard equipment of the fitting: clips made of stainless steel (INOX). TYTAN LED series has won the first prize in technical and commercial area lighting category during the 25th International Fair of Lighting Equipment LIGHT 2017 in Warsaw.

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.


# TYTAN LED ENDURA MINUS 1150MM 9000LM IP66 840 (56W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	56	Working temperature [°C]:	from -35 to +35
Index:	358043	Diffuser material:	PC
Colour temperature [K]:	4000	Material of the body:	PC
EAN:	5905963358043	Colour of the body:	grey
Luminous flux [lm]:	9000	Impact resistance:	IK09
Light source:	LED module	Ingress protection:	IP66
Diffuser type:	MAT	Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1152/85/80	Net weight [kg]:	1.520
Rated power of the luminaire [W]:	60	Warranty [years]:	5
Supply voltage [V]:	220-240	Version:	MINUS
Frequency [Hz]:	50 - 60	Category type:	battens
Luminous efficacy [lm/W]:	150	ETIM class:	EC000109
Energy efficiency class:	C	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Electrical protection class:	I	Warranty [years]:	5
Colour rendering index:	>80	CE certificate:	<a href="#">7/2017</a>
SDCM:	≤ 3	ENEC Certificate:	<a href="#">0310/ENEC/23</a>
Power factor:	0.98	PZH certificate:	<a href="#">HK/K/0199/01/2017</a>
LED lifespan L70B50 [h]:	74000	HACCP:	<a href="#">852/2004</a>
LED lifespan L80B20 [h]:	54000	Manual:	<a href="#">Download PDF</a>
LED lifespan L90B10 [h]:	31000		

## LIGHT CURVES



# TYTAN LED ENDURA MINUS 1150MM 9000LM IP66 840 (56W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
908231	TYTAN LED - holder
80000279	Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20\*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date:15 March 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 7/2017