

UP LED AS 2W 4000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	903007
Ingress protection:	IP65
Impact resistance:	IK08
Nominal power [W]:	2
Luminous flux [lm]*:	240
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	D
Material of the body:	plastic

CHARACTERISTICS

Energy-saving, outdoor 2W accent fitting provides economical and long-term operation without replacing light sources. Dustproof and waterproof luminaire with an ingress protection class of IP65, protected against dust and water splashing from a nozzle directed at any angle. Available with asymmetrical light distribution. Specification: color temperature of the LED light source: 3000K, 4000K.

APPLICATION

Outdoor luminaire intended to illuminate facades, stairs, alcoves, pillars and greenery in gardens, parks and recreational facilities.

UP LED AS 2W 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	2	Beam angle [°]:	60
Light source:	LED module	Diffuser material:	PC
Colour temperature [K]:	4000	Material of the body:	plastic
Luminous flux [lm]:	240	Mounting dimensions [mm]:	70/70/160
Rated power of the luminaire [W]:	2	Mounting version:	into the ground
Diffuser type:	PRM	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Net weight [kg]:	0.210
Ingress protection:	IP65	CE certificate:	187/2023
Frequency [Hz]:	50 - 60	Index:	903007
Impact resistance:	IK08	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	70/70/160	EAN:	5905963903007
Luminous efficacy [lm/W]:	120	Category type:	accent lighting
Energy efficiency class:	D	ETIM class:	EC000758
Electrical protection class:	II	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	Manual:	Download PDF
SDCM:	≤ 3	Plik LDT:	Pobierz
LED lifespan L70B50 [h]:	51000		

Card creation date: 20 May 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 187/2023