

VECTOR 3 LED 1441MM DALI RCR 5100LM PRM MAT IP40 840 (40W) CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK07
Nominal power [W]:	40
Luminous flux [lm]*:	5100
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	D
Material of the body:	powder coated steel
Diffuser material:	PC

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED GO! modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

VECTOR 3 LED 1441MM DALI RCR 5100LM PRM MAT IP40 840 (40W) CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	40	Impact resistance:	IK07
Light source:	LED module	Ingress protection:	IP40
Colour temperature [K]:	4000	Mounting version:	surface
Luminous flux [lm]:	5100	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	43.30	Net weight [kg]:	2.250
Diffuser type:	PRM MAT	Warranty [years]:	5
Motion sensor:	1	Index:	661693
Luminous efficacy [lm/W]:	118	EAN:	5905963661693
Corridor function:	1	Category type:	battens
Energy efficiency class:	D	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
DIMM DALI:	1	Supply voltage [V]:	220-240
Electrical protection class:	I	Frequency [Hz]:	50 - 60
Dimensions (H/W/T/S) [mm]:	1441/126/60	Flicker procent:	2
Colour rendering index:	>80	AC voltage range [V]:	198 - 264
SDCM:	≤ 3	CE certificate:	310/2023
Power factor:	0.95	LED lifespan L70B50 [h]:	116000
Diffuser material:	PC	LED lifespan L80B20 [h]:	72000
Material of the body:	powder coated steel	LED lifespan L90B10 [h]:	35000
Colour of the body:	white	Warranty [years]:	5
Mounting dimensions [mm]:	1330	Manual:	Download PDF
		Plik LDT:	Pobierz

Card creation date: 09 February 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 310/2023