

# VECTOR 3 LED 1441MM DALI RCR 6900LM PRM MAT IP40 840 (60W) CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK07
Nominal power [W]:	60
Luminous flux [lm]*:	6900
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PC

## CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED GO! modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

## APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

# VECTOR 3 LED 1441MM DALI RCR 6900LM PRM MAT IP40 840 (60W) CORRIDOR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Net weight [kg]:	2.250
Nominal power [W]:	60	Warranty [years]:	5
Rated power of the luminaire [W]:	62.50	Index:	661716
Luminous flux [lm]:	6900	EAN:	5905963661716
Luminous efficacy [lm/W]:	110	Category type:	battens
Energy efficiency class:	E	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Electrical protection class:	I	Supply voltage [V]:	220-240
Colour temperature [K]:	4000	Frequency [Hz]:	50 - 60
Colour rendering index:	80	Corridor function:	yes
SDCM:	≤ 3	Motion sensor:	yes
Power factor:	0.95	DIMM DALI:	yes
Diffuser material:	PC	Flicker procent:	10
Diffuser type:	PRM MAT	AC voltage range [V]:	198 - 264
Material of the body:	powder coated steel	CE certificate:	<a href="#">310/2023</a>
Colour of the body:	white	LED lifespan L70B50 [h]:	116000
Dimensions (H/W/T/S) [mm]:	1441/126/60	LED lifespan L80B20 [h]:	72000
Mounting dimensions [mm]:	1330	LED lifespan L90B10 [h]:	35000
Impact resistance:	IK07	Warranty [years]:	5
Ingress protection:	IP40	Manual:	<a href="#">Download PDF</a>
Mounting version:	surface	PZH certificate:	<a href="#">B-BK-60212-0019/20</a>
Working temperature [°C]:	from -20 to +35	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



Card creation date: 03 January 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 310/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)