

# VECTOR 3 LED 1441MM RCR 6900LM PRM MAT IP40 840 (60W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                 |                     |
|---------------------------------|---------------------|
| <b>Ingress protection:</b>      | IP40                |
| <b>Impact resistance:</b>       | IK07                |
| <b>Nominal power [W]:</b>       | 60                  |
| <b>Luminous flux [lm]*:</b>     | 6900                |
| <b>Colour temperature [K]:</b>  | 4000                |
| <b>Colour rendering index:</b>  | >80                 |
| <b>SDCM:</b>                    | ≤ 3                 |
| <b>Energy efficiency class:</b> | E                   |
| <b>Material of the body:</b>    | powder coated steel |
| <b>Diffuser material:</b>       | PC                  |

## CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED GO! modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

## APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

# VECTOR 3 LED 1441MM RCR 6900LM PRM MAT IP40 840 (60W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                     |                           |   |
|-----------------------------------|---------------------|---------------------------|---|
| Nominal power [W]:                | 60                  | Impact resistance:        | IK07  |
| Light source:                     | LED module          | Ingress protection:       | IP40  |
| Colour temperature [K]:           | 4000                | Mounting version:         | surface   |
| Luminous flux [lm]:               | 6900                | Working temperature [°C]: | from -20 to +35   |
| Rated power of the luminaire [W]: | 62.50               | Net weight [kg]:          | 2.150   |
| Diffuser type:                    | PRM MAT             | Warranty [years]:         | 5   |
| Motion sensor:                    | 1                   | Index:                    | 661471  |
| Luminous efficacy [lm/W]:         | 110                 | EAN:                      | 5905963661471   |
| Energy efficiency class:          | E                   | Category type:            | battens   |
| Electrical protection class:      | I                   | Photobiological safety:   | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Dimensions (H/W/T/S) [mm]:        | 1441/126/60         | Supply voltage [V]:       | 220-240   |
| Colour rendering index:           | >80                 | Frequency [Hz]:           | 50 - 60   |
| SDCM:                             | ≤ 3                 | Flicker procent:          | 2   |
| Power factor:                     | 0.95                | AC voltage range [V]:     | 198 - 264   |
| Diffuser material:                | PC                  | CE certificate:           | <a href="#">310/2023</a>  |
| Material of the body:             | powder coated steel | LED lifespan L70B50 [h]:  | 116000  |
| Colour of the body:               | white               | LED lifespan L80B20 [h]:  | 72000   |
| Mounting dimensions [mm]:         | 1330                | LED lifespan L90B10 [h]:  | 35000   |
|                                   |                     | Warranty [years]:         | 5   |
|                                   |                     | Manual:                   | <a href="#">Download PDF</a>  |
|                                   |                     | Plik LDT:                 | <a href="#">Pobierz</a>   |

Card creation date: 05 February 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 310/2023