

# OCULUS LED 22250LM 840 IP66 I KL. 75D SP10KV 141W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	963933
<b>Nominal power [W]:</b>	141
<b>Luminous flux [lm]*:</b>	22250
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	powder coated aluminium
<b>Diffuser material:</b>	PC
<b>Beam angle [°]:</b>	75
<b>Working temperature [°C]:</b>	from -25 to +60

## CHARACTERISTICS

OCULUS LED is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

## APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.


# OCULUS LED 22250LM 840 IP66 I KL. 75D SP10KV 141W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	141	Impact resistance:	IK09
Index:	963933	Ingress protection:	IP66
Colour temperature [K]:	4000	Mounting version:	suspended
Luminous flux [lm]:	22250	Cable length [m]:	0.30
Light source:	LED module	Dimensions of single box [mm]:	135/372/372
Diffuser material:	PC	Net weight [kg]:	3.428
Rated power of the luminaire [W]:	148.40	Category type:	high-bay and low-bay
Beam angle [°]:	75	AC voltage range [V]:	198-264
Frequency [Hz]:	50 - 60	DC voltage range [V]:	176-280
Working temperature [°C]:	from -25 to +60	LED lifespan L70B50 [h]:	196000
Luminous efficacy [lm/W]:	150	LED lifespan L80B20 [h]:	123000
Energy efficiency class:	C	LED lifespan L90B10 [h]:	60000
Colour rendering index:	>80	Accessories included:	Eye bolt
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.99	ETIM class:	EC001716
Surge protection [kV]:	4	The number of implement units:	1
Diffuser type:	transparent	Warranty [years]:	5
Diffuser colour:	transparent	ENEC Certificate:	<a href="#">PL BBJ/005/2021/M1</a>
Optics material:	PC	CE certificate:	<a href="#">153/2023</a>
Optics:	lens	PZH certificate:	<a href="#">B-BK-60212-0481/21</a>
Material of the body:	powder coated aluminium	HACCP:	<a href="#">852/2004</a>
Colour of the body:	grey	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	125/371	Pliik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# OCULUS LED 22250LM 840 IP66 I KL. 75D SP10KV 141W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor



OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)



OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)



OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 153/2023