

VECTOR 3 LED VD 1161MM RCR 5000LM PRM IP40 840 (41W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	661105
Ingress protection:	IP40
Impact resistance:	IK07
Nominal power [W]:	41
Luminous flux [lm]*:	5000
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	powder coated steel

CHARACTERISTICS

Surface-mounted luminaire made of powder-coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in the standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:
- motion sensor (RCR).

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings). The luminaire is intended for general areas inside buildings – store rooms and storage rack areas as well as cold stores included in tables 5.4 and 5.5 of the EN12464 standard; for indoor traffic zones included in table 5.1 of the EN12464 standard and for parking areas and as lighting of railway installations included in table 5.34 and 5.53 of the EN12464 standard, excluding ticket and luggage offices, counters, waiting rooms, entrance halls and lounges.


VECTOR 3 LED VD 1161MM RCR 5000LM PRM IP40 840 (41W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting dimensions [mm]:	1060
Nominal power [W]:	41	Impact resistance:	IK07
Rated power of the luminaire [W]:	45.50	Ingress protection:	IP40
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	5000	Motion sensor:	yes
Luminous efficacy [lm/W]:	109	Net weight [kg]:	1.500
Energy efficiency class:	E	Warranty [years]:	5
Electrical protection class:	I	CE certificate:	311/2023
Colour temperature [K]:	4000	Index:	661105
Color rendering index (Ra) >:	80	EAN:	5905963661105
SDCM:	3	Category type:	battens
Power factor:	0.99	AC voltage range [V]:	207 - 253
Max load (RCR) [W]:	400	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Surge protection [kV]:	2	LED lifespan L70B50 [h]:	135000
Diffuser material:	PC	LED lifespan L80B10 [h]:	85000
Diffuser type:	PRM	LED lifespan L90B10 [h]:	40000
Diffuser colour:	transparent	Warranty [years]:	5
Material of the body:	powder coated steel	Manual:	Download PDF
Colour of the body:	white	PZH certificate:	B-BK-60212-0019/20
Dimensions (H/W/T/S) [mm]:	1161/126/60	Plik LDT:	Download

LIGHT CURVES



Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 311/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl