

# VECTOR 3 LED VD 1441MM 7700LM PRM MAT IP40 840 (77W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	661020
Ingress protection:	IP40
Impact resistance:	IK07
Nominal power [W]:	77
Luminous flux [lm]*:	7700
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	Raw steel sheet, powder coated

## CHARACTERISTICS

Surface-mounted luminaire made of powder-coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in the standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:  
- motion sensor (RCR).

## APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings). The luminaire is intended for general areas inside buildings – store rooms and storage rack areas as well as cold stores included in tables 5.4 and 5.5 of the EN12464 standard; for indoor traffic zones included in table 5.1 of the EN12464 standard and for parking areas and as lighting of railway installations included in table 5.34 and 5.53 of the EN12464 standard, excluding ticket and luggage offices, counters, waiting rooms, entrance halls and lounges.


# VECTOR 3 LED VD 1441MM 7700LM PRM MAT IP40 840 (77W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting dimensions [mm]:	1330
Nominal power [W]:	77	Impact resistance:	IK07
Rated power of the luminaire [W]:	90	Ingress protection:	IP40
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	7700	Net weight [kg]:	1.900
Luminous efficacy [lm/W]:	85	Warranty [years]:	5
Energy efficiency class:	F	CE certificate:	<a href="#">311/2023</a>
Electrical protection class:	I	Index:	661020
Colour temperature [K]:	4000	EAN:	5905963661020
Colour rendering index:	>80	Category type:	battens
SDCM:	≤ 3	AC voltage range [V]:	207 - 253
Power factor:	0.99	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Surge protection [kV]:	2	LED lifespan L70B50 [h]:	135000
Diffuser material:	PC	LED lifespan L80B20 [h]:	85000
Diffuser type:	PRM MAT	LED lifespan L90B10 [h]:	40000
Diffuser colour:	mat	Warranty [years]:	5
Material of the body:	Raw steel sheet, powder coated	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white	PZH certificate:	<a href="#">B-BK-60212-0019/20</a>
Dimensions (H/W/T/S) [mm]:	1441/126/60	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



Card creation date: 03 January 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 311/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)