

VECTOR 3 LED VD 601MM RCR 3100LM PRM MAT IP40 840 (31W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	661068
Ingress protection:	IP40
Impact resistance:	IK07
Nominal power [W]:	31
Luminous flux [lm]*:	3100
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	powder coated steel

CHARACTERISTICS

Surface-mounted luminaire made of powder-coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in the standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:
- motion sensor (RCR).

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings). The luminaire is intended for general areas inside buildings – store rooms and storage rack areas as well as cold stores included in tables 5.4 and 5.5 of the EN12464 standard; for indoor traffic zones included in table 5.1 of the EN12464 standard and for parking areas and as lighting of railway installations included in table 5.34 and 5.53 of the EN12464 standard, excluding ticket and luggage offices, counters, waiting rooms, entrance halls and lounges.

VECTOR 3 LED VD 601MM RCR 3100LM PRM MAT IP40 840 (31W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK07
Nominal power [W]:	31	Ingress protection:	IP40
Rated power of the luminaire [W]:	36	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Motion sensor:	yes
Luminous flux [lm]:	3100	Net weight [kg]:	0.800
Luminous efficacy [lm/W]:	86	Warranty [years]:	5
Energy efficiency class:	F	CE certificate:	311/2023
Electrical protection class:	I	Index:	661068
Colour temperature [K]:	4000	EAN:	5905963661068
Colour rendering index:	80	Category type:	battens
SDCM:	≤ 3	AC voltage range [V]:	207 - 253
Power factor:	0.99	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Max load (RCR) [W]:	400	LED lifespan L70B50 [h]:	135000
Surge protection [kV]:	2	LED lifespan L80B20 [h]:	85000
Diffuser material:	PC	LED lifespan L90B10 [h]:	40000
Diffuser type:	PRM MAT	Warranty [years]:	5
Material of the body:	powder coated steel	Manual:	Download PDF
Colour of the body:	white	PZH certificate:	B-BK-60212-0019/20
Dimensions (H/W/T/S) [mm]:	601/126/60	Plik LDT:	Download
Mounting dimensions [mm]:	520		

LIGHT CURVES

