

VESPO LED 1161MM 4050LM PRM IP44 840 (27W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	639883
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	27
Luminous flux [lm]*:	4050
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	D
Material of the body:	powder coated steel

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

VESPO LED 1161MM 4050LM PRM IP44 840 (27W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44
Nominal power [W]:	27	Mounting version:	surface
Rated power of the luminaire [W]:	30.50	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Accessories included:	Mounting pads (2 pcs.)
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.300
Luminous flux [lm]:	4050	Index:	639883
Luminous efficacy [lm/W]:	132	EAN:	5905963639883
Energy efficiency class:	D	Category type:	battens
Electrical protection class:	I	AC voltage range [V]:	198 - 264
Colour temperature [K]:	4000	DC voltage range [V]:	176 – 280
Colour rendering index:	80	LED lifespan L70B50 [h]:	116000
SDCM:	≤ 3	LED lifespan L80B20 [h]:	72000
Power factor:	0.94	LED lifespan L90B10 [h]:	31000
Diffuser material:	PC	ETIM class:	EC000109
Diffuser type:	PRM	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	powder coated steel	Warranty [years]:	5
Colour of the body:	white	CE certificate:	332/2023
Dimensions (H/W/T/S) [mm]:	1161/124/60	PZH certificate:	B-BK-60212-0278/20
Mounting dimensions [mm]:	1060	Manual:	Download PDF
Impact resistance:	IK07	Plik LDT:	Download

LIGHT CURVES

