

# VESPO LED 1161MM 5650LM PRM MAT IP44 830 (50W)

## DETAILED CARD



### TECHNICAL PARAMETERS

Index:	639920
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	50
Luminous flux [lm]*:	5650
Colour temperature [K]:	3000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel

### CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

### APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

# VESPO LED 1161MM 5650LM PRM MAT IP44 830 (50W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44
Nominal power [W]:	50	Mounting version:	surface
Rated power of the luminaire [W]:	54.90	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Accessories included:	Mounting pads (2 pcs. )
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.300
Luminous flux [lm]:	5650	Index:	639920
Luminous efficacy [lm/W]:	102	EAN:	5905963639920
Energy efficiency class:	E	Category type:	battens
Electrical protection class:	I	AC voltage range [V]:	198 - 264
Colour temperature [K]:	3000	DC voltage range [V]:	176 – 280
Colour rendering index:	80	LED lifespan L70B50 [h]:	116000
SDCM:	≤ 3	LED lifespan L80B20 [h]:	72000
Power factor:	0.97	LED lifespan L90B10 [h]:	31000
Diffuser material:	PC	ETIM class:	EC000109
Diffuser type:	PRM MAT	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	white	Warranty [years]:	5
Material of the body:	powder coated steel	CE certificate:	<a href="#">332/2023</a>
Colour of the body:	white	PZH certificate:	<a href="#">B-BK-60212-0278/20</a>
Dimensions (H/W/T/S) [mm]:	1161/124/60	Manual:	<a href="#">Download PDF</a>
Mounting dimensions [mm]:	1060	Plik LDT:	<a href="#">Download</a>
Impact resistance:	IK07		

## LIGHT CURVES

