

# VESPO LED 1161MM AW 3200LM PRM MAT IP44 830 (27W)

## DETAILED CARD



### TECHNICAL PARAMETERS

Index:	643262
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	27
Luminous flux [lm]*:	3200
Colour temperature [K]:	3000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel

### CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

### APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

# VESPO LED 1161MM AW 3200LM PRM MAT IP44 830 (27W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK07
Nominal power [W]:	27	Ingress protection:	IP44
Rated power of the luminaire [W]:	30.53	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Emergency lighting [h]:	3
Luminous flux [lm]:	3200	Net weight [kg]:	2.500
Luminous efficacy [lm/W]:	104	Index:	643262
Energy efficiency class:	E	EAN:	5905963643262
Electrical protection class:	I	Category type:	battens
Colour temperature [K]:	3000	Autotest:	yes
Colour rendering index:	80	Operating mode:	M
SDCM:	≤ 3	AC voltage range [V]:	198 – 264
Power factor:	0.94	DC voltage range [V]:	176 – 280
Diffuser material:	PC	LED lifespan L70B50 [h]:	116000
Diffuser type:	PRM	LED lifespan L80B20 [h]:	72000
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	powder coated steel	Warranty [years]:	2 / 0.5 (bateria)
Colour of the body:	white	CE certificate:	<a href="#">332/2023</a>
Dimensions (H/W/T/S) [mm]:	1161/124/60	PZH certificate:	
Mounting dimensions [mm]:	1060	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES

