

VESPO LED 1161MM LS2 4150LM PRM MAT IP44 830 (34W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	643552
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	34
Luminous flux [lm]*:	4150
Colour temperature [K]:	3000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	D
Material of the body:	powder coated steel

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

VESPO LED 1161MM LS2 4150LM PRM MAT IP44 830 (34W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44
Nominal power [W]:	34	Mounting version:	surface
Rated power of the luminaire [W]:	35.80	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Accessories included:	Mounting pads (2 pcs.)
Frequency [Hz]:	50 - 60	Through wiring:	LS2
Luminous flux [lm]:	4150	Net weight [kg]:	2.450
Luminous efficacy [lm/W]:	115	Index:	643552
Energy efficiency class:	D	EAN:	5905963643552
Electrical protection class:	I	Category type:	battens
Colour temperature [K]:	3000	Operating mode:	M
Colour rendering index:	80	AC voltage range [V]:	198 – 264
SDCM:	≤ 3	DC voltage range [V]:	20-54
Power factor:	0.94	LED lifespan L70B50 [h]:	116000
Diffuser material:	PC	LED lifespan L80B20 [h]:	72000
Diffuser type:	PRM MAT	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	white	Warranty [years]:	5
Material of the body:	powder coated steel	CE certificate:	332/2023
Colour of the body:	white	PZH certificate:	B-BK-60212-0278/20
Dimensions (H/W/T/S) [mm]:	1161/124/60	Manual:	Download PDF
Mounting dimensions [mm]:	1060	Plik LDT:	Download
Impact resistance:	IK07		

LIGHT CURVES

