

# VESPO LED 1161MM LS2 5150LM PRM IP44 840 (34W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	643545
<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	34
<b>Luminous flux [lm]*:</b>	5150
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	powder coated steel

## CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

## APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).


# VESPO LED 1161MM LS2 5150LM PRM IP44 840 (34W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44
Nominal power [W]:	34	Mounting version:	surface
Rated power of the luminaire [W]:	35.80	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Accessories included:	Mounting pads (2 pcs. )
Frequency [Hz]:	50 - 60	Through wiring:	LS2
Luminous flux [lm]:	5150	Net weight [kg]:	2.450
Luminous efficacy [lm/W]:	143	Index:	643545
Energy efficiency class:	C	EAN:	5905963643545
Electrical protection class:	I	Category type:	battens
Colour temperature [K]:	4000	Operating mode:	M
Color rendering index (Ra) >:	80	AC voltage range [V]:	198 – 264
SDCM:	3	DC voltage range [V]:	20-54
Power factor:	0.94	LED lifespan L70B50 [h]:	116000
Diffuser material:	PC	LED lifespan L80B10 [h]:	72000
Diffuser type:	PRM	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	powder coated steel	Warranty [years]:	5
Colour of the body:	white	CE certificate:	<a href="#">332/2023</a>
Dimensions (H/W/T/S) [mm]:	1161/124/60	PZH certificate:	<a href="#">B-BK-60212-0278/20</a>
Mounting dimensions [mm]:	1060	Manual:	<a href="#">Download PDF</a>
Impact resistance:	IK07	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 332/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl