

VESPO LED 1161MM LS2 5650LM PRM MAT IP44 830 (50W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	643064
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	50
Luminous flux [lm]*:	5650
Colour temperature [K]:	3000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

VESPO LED 1161MM LS2 5650LM PRM MAT IP44 830 (50W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	50	Colour of the body:	white
Light source:	LED module	Mounting dimensions [mm]:	1060
Colour temperature [K]:	3000	Impact resistance:	IK07
Rated power of the luminaire [W]:	54.90	Ingress protection:	IP44
Luminous flux [lm]:	5650	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Diffuser type:	PRM MAT	Wire type:	5x2,5
Frequency [Hz]:	50 - 60	Accessories included:	Mounting pads (2 pcs.)
Luminous efficacy [lm/W]:	102	Net weight [kg]:	2.450
Operating mode:	M	Index:	643064
Energy efficiency class:	E	EAN:	5905963643064
Electrical protection class:	I	Category type:	battens
Through wiring:	LS2	Dusk sensor:	1
Dimensions (H/W/T/S) [mm]:	1161/124/60	AC voltage range [V]:	198 – 264
Colour rendering index:	>80	DC voltage range [V]:	176 - 280
SDCM:	≤ 3	LED lifespan L70B50 [h]:	116000
Power factor:	0.97	LED lifespan L80B20 [h]:	72000
Diffuser material:	PC	LED lifespan L90B10 [h]:	31000
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	powder coated steel	Warranty [years]:	5
		CE certificate:	332/2023
		PZH certificate:	B-BK-60212-0278/20
		Manual:	Download PDF
		Plik LDT:	Pobierz

Card creation date:13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 332/2023