VESPO LED 1161MM RCR 4800LM PRM IP44 830 (34W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	643491
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	34
Luminous flux [lm]*:	4800
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	D
Material of the body:	powder coated steel

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.
Available versions:
- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

VESPO LED 1161MM RCR 4800LM PRM IP44 830 (34W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	34
Rated power of the luminaire [W]:	35.80
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	4800
Luminous efficacy [lm/W]:	134
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.94
Max load (RCR) [W]:	400
Diffuser material:	PC
Diffuser type:	PRM
Material of the body:	powder coated steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	1161/124/60
Mounting dimensions [mm]:	1060
Impact resistance:	IK07

Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Motion sensor:	yes
Accessories included:	Mounting pads (2 pcs.)
Net weight [kg]:	2.300
Index:	643491
EAN:	5905963643491
Category type:	battens
Operating mode:	M
Dusk sensor:	yes
AC voltage range [V]:	198 – 264
DC voltage range [V]:	20-54
LED lifespan L70B50 [h]:	116000
LED lifespan L80B10 [h]:	72000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	332/2023
PZH certificate:	B-BK-60212-0278/20
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES



Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 332/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl