

VESPO LED 1441MM LS2 8450LM PRM MAT IP44 840 (71W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|---------------------|
| Index: | 643118 |
| Ingress protection: | IP44 |
| Impact resistance: | IK07 |
| Nominal power [W]: | 71 |
| Luminous flux [lm]*: | 8450 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | E |
| Material of the body: | powder coated steel |

CHARACTERISTICS

Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Available versions:

- motion sensor (RCR),
- DALI,
- through-wiring (LS2),
- emergency module.

APPLICATION

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings).

VESPO LED 1441MM LS2 8450LM PRM MAT IP44 840 (71W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------------|----------------------------------|---|
| Nominal power [W]: | 71 | Colour of the body: | white |
| Light source: | LED module | Mounting dimensions [mm]: | 1330 |
| Colour temperature [K]: | 4000 | Impact resistance: | IK07 |
| Rated power of the luminaire [W]: | 78 | Ingress protection: | IP44 |
| Luminous flux [lm]: | 8450 | Mounting version: | surface |
| Supply voltage [V]: | 220-240 | Working temperature [°C]: | from -20 to +35 |
| Diffuser type: | PRM MAT | Wire type: | 5x2,5 |
| Frequency [Hz]: | 50 - 60 | Accessories included: | Mounting pads (2 pcs.) |
| Luminous efficacy [lm/W]: | 108 | Net weight [kg]: | 3.100 |
| Operating mode: | M | Index: | 643118 |
| Energy efficiency class: | E | EAN: | 5905963643118 |
| Electrical protection class: | I | Category type: | battens |
| Through wiring: | LS2 | Dusk sensor: | 1 |
| Dimensions (H/W/T/S) [mm]: | 1441/124/60 | AC voltage range [V]: | 198 – 264 |
| Colour rendering index: | >80 | DC voltage range [V]: | 176 - 280 |
| SDCM: | ≤ 3 | LED lifespan L70B50 [h]: | 116000 |
| Power factor: | 0.98 | LED lifespan L80B20 [h]: | 72000 |
| Diffuser material: | PC | LED lifespan L90B10 [h]: | 31000 |
| Diffuser colour: | white | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Material of the body: | powder coated steel | Warranty [years]: | 5 |
| | | CE certificate: | 332/2023 |
| | | PZH certificate: | B-BK-60212-0278/20 |
| | | Manual: | Download PDF |
| | | Plik LDT: | Pobierz |

Card creation date:13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 332/2023