CAPELLA LED EDGE BOX RING VD 1400LM 840 IP54 RCR ANTHRACITE (16W) 340MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	953644
Ingress protection:	IP54
Impact resistance:	IK07
Nominal power [W]:	16
Luminous flux [lm]*:	1400
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED EDGE BOX RING VD 1400LM 840 IP54 RCR ANTHRACITE (16W) 340MM


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	16
Rated power of the luminaire [W]:	18
Supply voltage [V]:	220-240
Luminous flux [lm]:	1400
Luminous efficacy [lm/W]:	74
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Power factor:	0.98
Beam angle [°]:	120
Surge protection [kV]:	2
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	ABS
Colour of the body:	antracyt
Ring material:	ABS
Ring colour:	anthracite
Dimensions (H/W/T/S) [mm]:	340/105
Mounting dimensions [mm]:	160

Impact resistance:	IK07
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Motion sensor:	yes
Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Dimensions of single box [mm]:	342/342/122
Net weight [kg]:	0.820
Warranty [years]:	5
Flicker procent:	100
Index:	953644
Category type:	bulkheads
Category of application:	educational institutions
Rated power rating 30min [W]:	18
Luminous flux of the luminaire 0 min [lm]*:	1400
AC voltage range [V]:	220 - 240
ITHD [%]:	14
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
EDGE/BOX Colour:	anthracite
Warranty [years]:	5
Manual:	Download PDF

LIGHT CURVES



Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 156/2020

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl