

# EXPO SYSTEM LED FI 85 1100LM 15ST I KL IP20 WHITE (18W)

## FRESH MEAT

### DETAILED CARD



### TECHNICAL PARAMETERS

Index:	253614
Ingress protection:	IP20
Nominal power [W]:	18
Luminous flux [lm]*:	1100
Energy efficiency class:	G
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	lens
Mounting version:	track, surface

### CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors.

Available versions dedicated to lighting:  
meat, fresh meat, fruits and vegetables, fish and seafood, bread (gold), works of art (art), clothing (fashion).

Accessories:  
- base for surface mounting,  
- honeycomb that reduces glare.

### APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector

# EXPO SYSTEM LED FI 85 1100LM 15ST I KL IP20 WHITE (18W)


## FRESH MEAT

### DETAILED CARD

### TECHNICAL PARAMETERS TABLE

<b>Light source:</b>	LED module	<b>Dimensions (H/W/T/S) [mm]:</b>	Ø85/255
<b>Nominal power [W]:</b>	18	<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]:</b>	19.80	<b>Mounting version:</b>	track, surface
<b>Supply voltage [V]:</b>	220-240	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Frequency [Hz]:</b>	50 - 60	<b>Tilt angle adjustment [°]:</b>	355
<b>Luminous flux [lm]:</b>	1100	<b>Net weight [kg]:</b>	1.100
<b>Luminous efficacy [lm/W]:</b>	60	<b>CE certificate:</b>	45/2020
<b>Energy efficiency class:</b>	G	<b>Warranty [years]:</b>	2
<b>Electrical protection class:</b>	I	<b>Index:</b>	253614
<b>Beam angle [°]:</b>	15	<b>Category type:</b>	spotlight
<b>Diffuser material:</b>	PMMA	<b>Category of application:</b>	commercial facilities
<b>Diffuser type:</b>	lens	<b>Version:</b>	fresh meat
<b>Material of the body:</b>	aluminium	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Colour of the body:</b>	white	<b>Manual:</b>	<a href="#">Download PDF</a>

### LIGHT CURVES



# EXPO SYSTEM LED FI 85 1100LM 15ST I KL IP20 WHITE (18W)

## FRESH MEAT

### DETAILED CARD

### ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



EXPO SYSTEM LED honeycomb (255120)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 45/2020