EXPO SYSTEM LED FI 85 1100LM 24ST I KL IP20 WHITE (18W) MEAT

DETAILED CARD



TECHNICAL PARAMETERS

Index:	253669
Ingress protection:	IP20
Nominal power [W]:	18
Luminous flux [lm]*:	1100
Energy efficiency class:	G
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	lens
Mounting version:	track, surface

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors.

Available versions dedicated to lighting:

meat, fresh meat, fruits and vegetables, fish and seafood, bread (gold), works of art (art), clothing (fashion).

Accessories:

- base for surface mounting,
- honeycomb that reduces glare.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector




EXPO SYSTEM LED FI 85 1100LM 24ST I KL IP20 WHITE (18W) MEAT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	Ø85/255
Nominal power [W]:	18	Ingress protection:	IP20
Rated power of the luminaire [W]:	19.80	Mounting version:	track, surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Tilt angle adjustment [°]:	355
Luminous flux [lm]:	1100	Net weight [kg]:	1.100
Luminous efficacy [lm/W]:	60	CE certificate:	45/2020
Energy efficiency class:	G	Warranty [years]:	2
Electrical protection class:	1	Index:	253669
Beam angle [°]:	24	Category type:	spotlight
Diffuser material:	РММА	Category of application:	commercial facilities
Diffuser type:	lens	Version:	meat
Material of the body:	aluminium	Photobiological safety:	Risk Group 1 (no photobiological
Colour of the body:	white		hazard under normal behavioral limitation)
		Manual:	Download PDF

LIGHT CURVES



EXPO SYSTEM LED FI 85 1100LM 24ST I KL IP20 WHITE (18W) MEAT

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



Certificate CE - Nr: 45/2020

EXPO SYSTEM LED honeycomb (255120)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).

