# EXPO SYSTEM LED FI 85 3100LM 24ST I KL IP20 WHITE (28W) FISH

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

**Index:** 253515

Ingress protection: IP20

Nominal power [W]: 28

Luminous flux [lm]\*: 3100

Energy efficiency class:

Material of the body: aluminium

Diffuser material: PMMA

**Diffuser type:** lens

Mounting version: track, surface

## **CHARACTERISTICS**

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors.

Available versions dedicated to lighting: meat, fresh meat, fruits and vegetables, fish and seafood, bread (gold), works of art (art), clothing (fashion).

### Accessories:

- base for surface mounting,
- honeycomb that reduces glare.

### **APPLICATION**

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector



# EXPO SYSTEM LED FI 85 3100LM 24ST I KL IP20 WHITE (28W) FISH


**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Light source:	LED module	
Nominal power [W]:	28	
Rated power of the luminaire [W]:	29	
Supply voltage [V]:	220-240	
Frequency [Hz]:	50 - 60	
Luminous flux [Im]:	3100	
Luminous efficacy [lm/W]:	107	
Energy efficiency class:	E	
Electrical protection class:	1	
Beam angle [°]:	24	
Diffuser material:	PMMA	
Diffuser type:	lens	
Material of the body:	aluminium	
Colour of the body:	white	

Dimensions (H/W/T/S) [mm]:	Ø85/255	
Ingress protection:	IP20	
Mounting version:	track, surface	
Working temperature [°C]:	from -20 to +35	
Tilt angle adjustment [°]:	355	
Net weight [kg]:	1.100	
CE certificate:	45/2020	
Warranty [years]:	2	
Index:	253515	
Category type:	spotlight	
Category of application:	commercial facilities	
Version:	fish and seafood	
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)	
Manual:	Download PDF	

## **LIGHT CURVES**



# EXPO SYSTEM LED FI 85 3100LM 24ST I KL IP20 WHITE (28W) FISH


**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



EXPO SYSTEM LED honeycomb (255120)

