

ASTRA LED 12-24V 2630/2200LM 840 IP66 III KL. CORD 0.2M 19W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	663277
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	19
Luminous flux of the luminaire [lm] - range:	2630/2200
Colour temperature [K]:	4000
SDCM:	≤ 3
Colour rendering index:	>80
Electrical protection class:	III
Energy efficiency class:	C

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom).

The luminaire is adapted to supply voltage from solar panels, wind turbines, or other sources with an output voltage of 12-24V DC. The luminous flux parameter is given for two values 12V and 24V DC.

APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and Mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.


ASTRA LED 12-24V 2630/2200LM 840 IP66 III KL. CORD 0.2M 19W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	663277	Ingress protection:	IP66
Rated power of the luminaire [W]:	19	Working temperature [°C]:	from -20 to +35
Luminous flux of the luminaire [lm] - range:	2630/2200	Tilt angle adjustment [°]:	-5 to +15 (peak to pole); -15 to +5 (side to boom)
Luminous efficacy [lm/W]:	149	Lateral surface (SCx) [m2]:	0.018
Energy efficiency class:	C	Wire type:	H07RN-F 2x1.5
Electrical protection class:	III	Cable length [m]:	0.30
Colour temperature [K]:	4000	Number on the palette [pcs]:	62
Colour rendering index:	>80	Net weight [kg]:	1.850
SDCM:	≤ 3	DC voltage range [V]:	12 - 24
Diffuser material:	PC	LED lifespan L70B50 [h]:	136000
Diffuser type:	matrix led	LED lifespan L80B20 [h]:	86000
Diffuser colour:	transparent	LED lifespan L90B10 [h]:	41000
Optics material:	PC	Category type:	street lighting
Optics:	matrix lens	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP+FG	ULOR:	0%
Dimensions (H/W/T/S) [mm]:	640/233/113	Warranty [years]:	6
Mounting dimensions [mm]:	ø60	CE certificate:	99/2023
Impact resistance:	IK08	Manual:	Download PDF

LIGHT CURVES



ASTRA LED 12-24V 2630/2200LM 840 IP66 III KL. CORD 0.2M 19W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
UL00229	mounting grip 78 mm



mounting grip 78 mm (UL00229)

Card creation date: 05 February 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 99/2023