

PORTAL LED BASIC HV 6W PC EXTERNAL DUSK SENSOR 4000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	6
Luminous flux [lm]*:	440
Colour temperature [K]:	3000; 4000
SDCM:	≤ 4
Energy efficiency class:	F; G
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

Surface mounted, rectangle LED light fixture with a high luminous flux, ingress protection class IP54 and an integrated energy-saving light source LED GO!. White ABS base; diffuser made of impact resistant PC provides even light distribution and ensures a high impact resistance class (IK08).

APPLICATION

Surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways, staircases) as well as outdoor use (façade lighting). The version with a radio motion sensor (RCR) is particularly well-suited to be used as a light source for public rooms and buildings (civic buildings, apartment buildings).

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.


PORTAL LED BASIC HV 6W PC EXTERNAL DUSK SENSOR 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Colour of the body:	biały
Nominal power [W]:	6	Dimensions (H/W/T/S) [mm]:	280/185/55
Rated power of the luminaire [W]:	6	Impact resistance:	IK08
Supply voltage [V]:	220-240	Ingress protection:	IP54
Frequency [Hz]:	50-60	Mounting version:	natynkowy
Luminous flux [lm]:	440	Working temperature [°C]:	od -20 do +35; od -25 do +35
Luminous efficacy [lm/W]:	62	Net weight [kg]:	0.520; 0.570
Energy efficiency class:	F; G	Warranty [years]:	3
Electrical protection class:	I	CE certificate:	404/2023; 56/2020
Colour temperature [K]:	3000; 4000	Index:	x
Colour rendering index:	>80	EAN:	x
SDCM:	≤ 4	Category type:	bulkheads
Power factor:	0.53	Dusk sensor:	yes
LED lifespan L70B50 [h]:	50000	Luminaire rated power 0min [W]:	6
Beam angle [°]:	120	ETIM class:	EC002892
Diffuser material:	PC	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Diffuser type:	OPAL	Manual:	Download PDF
Material of the body:	PP		

LIGHT CURVES



Card creation date: 17 August 2021
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 404/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl