

# DIONE LED PLUS ASYMMETRIC 2150LM 830 IP65 I KL. DALI RCR OPAL WHITE 21W CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	952197
Nominal power [W]:	21
Luminous flux [lm]*:	2150
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


# DIONE LED PLUS ASYMMETRIC 2150LM 830 IP65 I KL. DALI RCR OPAL WHITE 21W CORRIDOR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	952197	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65
Nominal power [W]:	21	Mounting version:	surface
Rated power of the luminaire [W]:	22	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Corridor function:	yes
Frequency [Hz]:	50 - 60	Motion sensor:	yes
Luminous flux [lm]:	2150	DIMM DALI:	yes
Luminous efficacy [lm/W]:	98	Dimensions of single box [mm]:	340/340/115
Energy efficiency class:	E	Net weight [kg]:	1
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	3000	Permeability factor of the diffuser:	0.80
Colour rendering index:	80	Category type:	bulkheads
SDCM:	≤ 3	Category of application:	educational institutions, commercial facilities
Power factor:	0.94	AC voltage range [V]:	198 - 264
Beam angle [°]:	120	DC voltage range [V]:	176 - 280
Surge protection [kV]:	1	LED lifespan L70B50 [h]:	115000
Diffuser material:	PC	LED lifespan L80B20 [h]:	75000
Diffuser type:	OPAL	LED lifespan L90B10 [h]:	33000
Diffuser colour:	white	Light distribution type:	asymmetric
Optics material:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS	CE certificate:	<a href="#">380/2023</a>
Colour of the body:	white	Warranty [years]:	5
Ring material:	ABS	Manual:	<a href="#">Download PDF</a>
Ring colour:	white	PZH certificate:	<a href="#">B-BK-60212-0619/20</a>
Dimensions (H/W/T/S) [mm]:	340/115	ENEC Certificate:	<a href="#">PL BBJ/011/2021/M1/A1</a>
Mounting dimensions [mm]:	140	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# DIONE LED PLUS ASYMMETRIC 2150LM 830 IP65 I KL. DALI RCR OPAL WHITE 21W CORRIDOR

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white  
matt RAL 9003 painted vandal  
resistant (120DL118)

Card creation date:10 June 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 380/2023