

DIONE LED PLUS ASYMMETRIC 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	952227
Nominal power [W]:	32
Luminous flux [lm]*:	3200
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	32	Ingress protection:	IP65
Index:	952227	Mounting version:	surface
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	3200	Motion sensor:	1
Light source:	LED module	DIMM DALI:	1
Diffuser type:	OPAL	Corridor function:	1
Rated power of the luminaire [W]:	33	Emergency lighting [h]:	0
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	340/340/115
Frequency [Hz]:	50 - 60	Net weight [kg]:	1
Luminous efficacy [lm/W]:	97	Warranty [years]:	5
Energy efficiency class:	E	Permeability factor of the diffuser:	0.80
Electrical protection class:	I	Category type:	bulkheads
Colour rendering index:	>80	Category of application:	commercial facilities, educational institutions
SDCM:	≤ 3	AC voltage range [V]:	198 - 264
Power factor:	0.94	DC voltage range [V]:	176 - 280
Beam angle [°]:	120	LED lifespan L70B50 [h]:	115000
Surge protection [kV]:	1	LED lifespan L80B20 [h]:	75000
Diffuser material:	PC	LED lifespan L90B10 [h]:	33000
Diffuser colour:	white	Light distribution type:	asymmetric
Optics material:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS	CE certificate:	380/2023
Colour of the body:	white	Warranty [years]:	5
Ring material:	ABS	Manual:	Download PDF
Ring colour:	white	PZH certificate:	B-BK-60212-0619/20
Dimensions (H/W/T/S) [mm]:	340/115	ENEC Certificate:	PL BBJ/011/2021/M1/A1
Mounting dimensions [mm]:	140	Plik LDT:	Pobierz
Impact resistance:	IK10		

DIONE LED PLUS ASYMMETRIC 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 26 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 380/2023