

# DIONE LED PLUS ASYMMETRIC 3200LM 840 IP65 I KL. OPAL WHITE 32W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	952814
<b>Nominal power [W]:</b>	32
<b>Luminous flux [lm]*:</b>	3200
<b>Colour temperature [K]:</b>	4000
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Ring material:</b>	ABS
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

# DIONE LED PLUS ASYMMETRIC 3200LM 840 IP65 I KL. OPAL WHITE 32W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	952814	Mounting dimensions [mm]:	140
Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	32	Ingress protection:	IP65
Rated power of the luminaire [W]:	33	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	340/340/115
Luminous flux [lm]:	3200	Net weight [kg]:	1
Luminous efficacy [lm/W]:	97	Warranty [years]:	5
Energy efficiency class:	E	Permeability factor of the diffuser:	0.80
Electrical protection class:	I	Category type:	bulkheads
Colour temperature [K]:	4000	Category of application:	educational institutions, commercial facilities
Color rendering index (Ra) >:	80	AC voltage range [V]:	198 - 264
SDCM:	3	DC voltage range [V]:	176 - 280
Power factor:	0.90	LED lifespan L70B50 [h]:	115000
Beam angle [°]:	120	LED lifespan L80B10 [h]:	75000
Surge protection [kV]:	1	LED lifespan L90B10 [h]:	33000
Diffuser material:	PC	Light distribution type:	asymmetric
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	white	CE certificate:	<a href="#">380/2023</a>
Optics material:	ABS	Warranty [years]:	5
Material of the body:	ABS	ENEC Certificate:	<a href="#">PL BBJ/01/2021/M1/A1</a>
Colour of the body:	white	Environmental Product Declaration (EPD):	<a href="#">944/2026</a>
Ring material:	ABS	Manual:	<a href="#">Download PDF</a>
Ring colour:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	340/115	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# DIONE LED PLUS ASYMMETRIC 3200LM 840 IP65 I KL. OPAL WHITE 32W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white  
matt RAL 9003 painted vandal  
resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 380/2023