

DIONE LED PLUS ASYMMETRIC P 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	952340
Nominal power [W]:	32
Luminous flux [lm]*:	3200
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC P 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	952340	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Nominal power [W]:	32	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	33	Corridor function:	yes
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	3200	Dimensions of single box [mm]:	340/340/115
Luminous efficacy [lm/W]:	97	Net weight [kg]:	1
Energy efficiency class:	E	Warranty [years]:	5
Electrical protection class:	I	Permeability factor of the diffuser:	0.80
Colour temperature [K]:	4000	Category type:	bulkheads
Color rendering index (Ra) >:	80	Category of application:	educational institutions, commercial facilities
SDCM:	3	Version:	P
Power factor:	0.94	AC voltage range [V]:	198 - 264
Beam angle [°]:	120	DC voltage range [V]:	176 - 280
Surge protection [kV]:	1	LED lifespan L70B50 [h]:	115000
Diffuser material:	PC	LED lifespan L80B10 [h]:	75000
Diffuser type:	OPAL	LED lifespan L90B10 [h]:	33000
Diffuser colour:	white	Light distribution type:	asymmetric
Optics material:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS	CE certificate:	380/2023
Colour of the body:	white	Warranty [years]:	5
Ring material:	ABS	ENEC Certificate:	PL BBJ/011/2021/M1/A1
Ring colour:	white	Environmental Product Declaration (EPD):	944/2026
Dimensions (H/W/T/S) [mm]:	340/115	Manual:	Download PDF
Mounting dimensions [mm]:	140	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Impact resistance:	IK10	Plik LDT:	Download

DIONE LED PLUS ASYMMETRIC P 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR

DETAILED CARD LIGHT CURVES



DIONE LED PLUS ASYMMETRIC P 3200LM 840 IP65 I KL. DALI RCR OPAL WHITE 32W CORRIDOR

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 380/2023