CAPELLA LED PLUS EDGE BOX RING 2450LM 840 IP54 PIR WHITE (26W) 340MM

DETAILED CARD





TECHNICAL PARAMETERS

Index:	953750
Ingress protection:	IP54
Impact resistance:	IK07
Nominal power [W]:	26
Luminous flux [lm]*:	2450
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor.
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.



CAPELLA LED PLUS EDGE BOX RING 2450LM 840 IP54 PIR WHITE (26W) 340MM


DETAILED CARD

TECHNICAL PARAMETERS TABLE

	1.55
Light source:	LED module
Nominal power [W]:	26
Rated power of the luminaire [W]:	28
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	2450
Luminous efficacy [lm/W]:	88
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.93
LED lifespan L70B50 [h]:	120000
Beam angle [°]:	120
Surge protection [kV]:	2
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	ABS
Colour of the body:	white
Ring material:	ABS
Ring colour:	white

Dimensions (H/W/T/S) [mm]: Mounting dimensions [mm]: Impact resistance: Ingress protection: Ingress protection: Working temperature [°C]: PIR: Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: Index: 158 IK07 IP54 Surface from -10 to +35 yes gland, extraction, 2x cover cable, screws, wall plugs 6mm 342/342/122 1.850 Varranty [years]: 5 CE certificate: 374/2023 Index: 953750
Impact resistance: Ingress protection: Ingress protection: Mounting version: Working temperature [°C]: PIR: Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: IK07 IR07 IR07 IR07 IP54 Surface from -10 to +35 yes gland, extraction, 2x cover cable, screws, wall plugs 6mm 342/342/122 1.850 Varranty [years]: 5 CE certificate: 374/2023
Ingress protection: IP54 Mounting version: Working temperature [°C]: PIR: yes Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: IP54 from -10 to +35 yes gland, extraction, 2x cover cable, screws, wall plugs 6mm 342/342/122 1.850 Warranty [years]: 5 CE certificate: 374/2023
Mounting version: Working temperature [°C]: PIR: Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: surface from -10 to +35 yes gland, extraction, 2x cover cable, screws, wall plugs 6mm 342/342/122 1.850 5 CE certificate: 374/2023
Working temperature [°C]: from -10 to +35 PIR: yes Accessories included: gland, extraction, 2x cover cable, screws, wall plugs 6mm Dimensions of single box [mm]: 342/342/122 Net weight [kg]: 1.850 Warranty [years]: 5 CE certificate: 374/2023
PIR: Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: yes gland, extraction, 2x cover cable, screws, wall plugs 6mm 342/342/122 1.850 5 CE certificate: 374/2023
Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: gland, extraction, 2x cover cable, screws, wall plugs 6mm 342/342/122 1.850 5 CE certificate: 374/2023
Accessories included: Dimensions of single box [mm]: Net weight [kg]: Warranty [years]: CE certificate: Screws, wall plugs 6mm 342/342/122 1.850 5 CE certificate: 374/2023
Net weight [kg]: 1.850 Warranty [years]: 5 CE certificate: 374/2023
Warranty [years]: 5 CE certificate: 374/2023
CE certificate: <u>374/2023</u>
<u></u>
Index: 953750
Category type: bulkheads
Version: EDGE BOX RING
AC voltage range [V]: 198 - 264
UGR (4H8H): 17.5
Dimensions of bulk box (H/W/D) [mm]: 794/1194/982
Photobiological safety: Risk Group 1 (no photobiological hazard under normal behavioral limitation)
EDGE/BOX Colour: white
Manual: Download PDF
Plik LDT: Download

LIGHT CURVES





CAPELLA LED PLUS EDGE BOX RING 2450LM 840 IP54 PIR WHITE (26W) 340MM

DETAILED CARD

TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 27 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

