CAPELLA LED PLUS EDGE Z 1500LM 840 IP20 (15W) 320MM

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	15
Luminous flux [lm]*:	1500
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PC
Diffuser type:	OPAL
Optics material:	PMMA

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

Versions available on request:

- any RAL colour of the body,
- any RAL colour of the suspension system,
- selected colours of the material of the cable.

Next versions (available soon):

- IoT (adapted for integration with additional control systems).

APPLICATION

Suspended luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE Z 1500LM 840 IP20 (15W) 320MM


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	15
Rated power of the luminaire [W]:	16
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1500
Luminous efficacy [lm/W]:	94
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.94
LED lifespan L70B50 [h]:	115000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	white
Optics material:	PMMA
Optics:	lens
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	320/177/2200

Mounting dimensions [mm]:	45
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -10 to +35
Wire type:	transparent
Cable length [m]:	2
Accessories included:	6mm dowels
Dimensions of single box [mm]:	320/320/220
Net weight [kg]:	1.200
CE certificate:	162/2018
Index:	951251
EAN:	5905963951251
Category type:	bulkheads
Version:	EDGE
Luminaire rated power 0min [W]:	15.47
AC voltage range [V]:	220-240
UGR (4H8H):	17,5-25,2
Light distribution type:	lambertian
Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES



CAPELLA LED PLUS EDGE Z 1500LM 840 IP20 (15W) 320MM

DETAILED CARD

TECHNICAL DETAILS



capella led z biała zwiesie

Card creation date: 19 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 162/2018

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl