

# DL 220 LED EVO VD 220MM 800 LM 830 PRM (10W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	657528
Ingress protection:	IP65/20
Nominal power [W]:	10
Luminous flux [lm]*:	800
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	F
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC

## CHARACTERISTICS

Round LED recessed mounted downlight, even light distribution and high ingress protection class IP65 (diffuser), IP40 (top) equipped with an integrated energysaving light source LED GO! Product made from ABS plastic combined with PC diffuser.

## APPLICATION

Luminaire designed for downlighting, especially in moist and humid applications. Luminaire designed for both indoor and outdoor use. Evenly diffused light provides optimal and comfort lighting for medical, healthcare and laboratory rooms, industrial facilities as well as bathrooms, swimming pools or toilets. Due to the possibility of making it compatible with external lighting systems, it is also recommended to A class buildings. Designed for mounting in each type of suspended ceiling (modular, plasterboard).

# DL 220 LED EVO VD 220MM 800 LM 830 PRM (10W)

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	657528	Dimensions (H/W/T/S) [mm]:	220/85
Light source:	LED module	Mounting dimensions [mm]:	205
Nominal power [W]:	10	Impact resistance:	IK08
Rated power of the luminaire [W]:	10	Ingress protection:	IP65/20
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -15 to +35
Luminous flux [lm]:	800	Net weight [kg]:	0.450
Luminous efficacy [lm/W]:	78	Warranty [years]:	5
Energy efficiency class:	F	Category type:	downlights
Electrical protection class:	I	Category of application:	commercial facilities, medical facilities
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	113000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	72000
Power factor:	0.98	LED lifespan L90B10 [h]:	34000
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	PRM	CE certificate:	69/2020
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white		

Card creation date: 27 March 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 69/2020