

DIONE LED PLUS ASYMMETRIC P 2150-3000LM 830 IP65 I KL. OPAL WHITE MULTI LED

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|----------------|
| Ingress protection: | IP65 |
| Impact resistance: | IK10 |
| Nominal power [W] - range: | 21/27/32 |
| Colour temperature [K]: | 3000 |
| Luminous flux of the luminaire [lm] - range: | 2150/2650/3000 |
| SDCM: | 3 |
| Energy efficiency class: | E |
| Material of the body: | ABS |
| Ring material: | ABS |
| Diffuser material: | PC |

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of three settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC P 2150-3000LM 830 IP65 I KL. OPAL WHITE MULTI LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|----------------|--|---|
| Index: | 952234 | Impact resistance: | IK10 |
| Light source: | LED module | Ingress protection: | IP65 |
| Supply voltage [V]: | 220-240 | Mounting version: | surface |
| Frequency [Hz]: | 50 - 60 | Working temperature [°C]: | from -20 to +35 |
| Energy efficiency class: | E | Dimensions of single box [mm]: | 340/340/115 |
| Electrical protection class: | I | Net weight [kg]: | 1.100 |
| Nominal power [W] - range: | 21/27/32 | Warranty [years]: | 5 |
| Colour temperature [K]: | 3000 | Permeability factor of the diffuser: | 0.73 |
| Luminous flux of the luminaire [lm] - range: | 2150/2650/3000 | Category type: | bulkheads |
| Color rendering index (Ra) >: | 80 | Category of application: | educational institutions, commercial facilities |
| SDCM: | 3 | AC voltage range [V]: | 198-264 |
| Power factor: | 0.93 | LED lifespan L70B50 [h]: | 115000 |
| Beam angle [°]: | 120 | LED lifespan L80B10 [h]: | 75000 |
| Surge protection [kV]: | 1 | LED lifespan L90B10 [h]: | 33000 |
| Diffuser material: | PC | Version: | P |
| Diffuser type: | OPAL | Light distribution type: | asymmetric |
| Diffuser colour: | white | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Material of the body: | ABS | CE certificate: | 381/2023 |
| Colour of the body: | white | Environmental Product Declaration (EPD): | 944/2026 |
| Ring material: | ABS | Manual: | Download PDF |
| Ring colour: | white | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| Dimensions (H/W/T/S) [mm]: | 340/115 | Pliik LDT: | Download |
| Mounting dimensions [mm]: | 140 | | |

LIGHT CURVES



DIONE LED PLUS ASYMMETRIC P 2150-3000LM 830 IP65 I KL. OPAL WHITE MULTI LED

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|----------|---|
| 120DL118 | Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant |



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 381/2023