

DIONE LED PLUS ASYMMETRIC DP 2150-3000LM 830 IP65 I KL. RCR OPAL WHITE MULTI LED

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W] - range:	21/27/32
Colour temperature [K]:	3000
Luminous flux of the luminaire [lm] - range:	2150/2650/3000
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of three settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC DP 2150-3000LM 830 IP65 I KL. RCR OPAL WHITE MULTI LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	952371	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Energy efficiency class:	E	Motion sensor:	yes
Electrical protection class:	I	Dimensions of single box [mm]:	340/340/115
Nominal power [W] - range:	21/27/32	Net weight [kg]:	1.150
Colour temperature [K]:	3000	Warranty [years]:	5
Luminous flux of the luminaire [lm] - range:	2150/2650/3000	Permeability factor of the diffuser:	0.73
Color rendering index (Ra) >:	80	Category type:	bulkheads
SDCM:	3	Category of application:	educational institutions, commercial facilities
Power factor:	0.93	AC voltage range [V]:	198-264
Beam angle [°]:	120	LED lifespan L70B50 [h]:	115000
Surge protection [kV]:	1	LED lifespan L80B10 [h]:	75000
Diffuser material:	PC	LED lifespan L90B10 [h]:	33000
Diffuser type:	OPAL	Version:	DP
Diffuser colour:	white	Light distribution type:	asymmetric
Material of the body:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	CE certificate:	381/2023
Ring material:	ABS	Environmental Product Declaration (EPD):	944/2026
Ring colour:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	340/115	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Mounting dimensions [mm]:	140	Plik LDT:	Download

LIGHT CURVES



DIONE LED PLUS ASYMMETRIC DP 2150-3000LM 830 IP65 I KL. RCR OPAL WHITE MULTI LED

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 381/2023