

MIMO 2 LED 1230MM 3600LM IP66 840 (23W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	100864
Ingress protection:	IP66
Impact resistance:	IK06
Luminaire rated power P_{min} [W]:	23.70
Luminous flux [lm]*:	3600
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	C
Material of the body:	PC

CHARACTERISTICS

MIMO 2 LED represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED panels offering the best lighting level required and energy savings of up to 66%. The multilayer shade has been made of UV-resistant polycarbonate. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 150 lm/W. Optional: Through-Wiring series connection - LS2.

APPLICATION

The multifunctional LED luminaire is designed for use in areas with increased dust and humidity. It is particularly suitable for industrial conditions, car parks (underground and multi-storey ones), sports stadiums, warehouses, transport terminals and underground passages. The luminaire is used both in new applications, as well as in replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended installation using standard equipment.

MIMO 2 LED 1230MM 3600LM IP66 840 (23W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	100864	Ingress protection:	IP66
Nominal power [W]:	23	Mounting version:	surface, suspended
EAN:	50095963100864	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	4000	Net weight [kg]:	0.300
Light source:	LED module	CE certificate:	151/2023
Luminous flux [lm]:	3600	Category type:	battens
Diffuser type:	MAT	Operating mode:	M
Rated power of the luminaire [W]:	23.70	AC voltage range [V]:	207 - 253
Supply voltage [V]:	220-240	Luminous efficacy [lm/W]:	152
Dimensions (H/W/T/S) [mm]:	1230/45/50	Electrical protection class:	II
Frequency [Hz]:	50 - 60	Power factor:	0.92
Energy efficiency class:	C	LED lifespan L70B50 [h]:	143000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	90000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	41000
Surge protection [kV]:	1	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser material:	PC	Warranty [years]:	5
Material of the body:	PC	Warranty [years]:	5
Colour of the body:	white	Manual:	Download PDF
Mounting dimensions [mm]:	800	ETIM class:	EC000109
Impact resistance:	IK06	Plik LDT:	Pobierz

MIMO 2 LED 1230MM 3600LM IP66 840 (23W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
100673	MIMO 2 LED - double handle (set)
800ML208	IP68 High-bay PA 6.6 connector black DL06-3A-2Y



MIMO 2 LED - double handle (set) (100673)



IP68 High-bay PA 6.6 connector black DL06-3A-2Y (800ML208)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 151/2023