

# LINEA 2 LED 3360MM 16000LM LS2 5P 840 60D (102W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	966545
<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK06
<b>Nominal power [W]:</b>	102
<b>Luminous flux [lm]*:</b>	16000
<b>Colour temperature [K]:</b>	4000
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey

## CHARACTERISTICS

LINEA 2 LED is the NEXT GEN pendant and surface-mounted lighting line system, a new generation of lamps dedicated to LED technology. The innovative connection system and pass-through cabling allow the luminaires to be quickly combined into a lighting line. The design used allows for easy assembly and power connection. The aluminium profile body, made from scratch, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. Diodes from a renowned manufacturer integrated in redesigned, completely new modules contribute to a very high luminous efficacy: up to 157 lm/W. This guarantees that the required illuminance level is achieved and significant energy savings are made. The optics are made of UV-resistant PMMA. Thanks to the use of linear lenses, adaptation to different lighting requirements is possible - 3 distribution angles: 90, 60, 45.

## APPLICATION

Particularly well suited for indoor use. Dedicated as the primary light source for commercial facilities, manufacturing plants and warehouses. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy-saving LED solutions.


# LINEA 2 LED 3360MM 16000LM LS2 5P 840 60D (102W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK06
Nominal power [W]:	102	Ingress protection:	IP20
Rated power of the luminaire [W]:	102	Mounting version:	surface, suspended
Supply voltage [V]:	220-240	Through wiring:	LS2 5P
Frequency [Hz]:	50 - 60	Net weight [kg]:	3.990
Luminous flux [lm]:	16000	Warranty [years]:	5
Luminous efficacy [lm/W]:	146	Index:	966545
Energy efficiency class:	C	Category type:	systems
Electrical protection class:	I	Category of application:	HoReCa, commercial facilities, industrial
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	103000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	65000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	32000
Beam angle [°]:	60	CE certificate:	<a href="#">170/2023</a>
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Warranty [years]:	5
Material of the body:	aluminium	Working temperature [°C]:	from -15 to +35
Colour of the body:	grey	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	47/52/3360	ENEC Certificate:	<a href="#">0334/ENEC/23</a>

## LIGHT CURVES




# LINEA 2 LED 3360MM 16000LM LS2 5P 840 60D (102W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
966309	LINEA 2 LED 1680mm - LS2 5P blank module
966316	LINEA 2 LED 1680mm - LS2 7P blank module
966644	LINEA 2 LED 3360mm - LS2 5P blank module
966651	LINEA 2 LED 3360mm - LS2 7P blank module
966323	LINEA 2 LED - closing set
966330	LINEA 2 LED - 840mm cover



LINEA 2 LED - closing set (966323)

Card creation date: 09 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 170/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl