

LINEA 2 LED 3360MM 7500LM DALI LS2 7P 840 90D (48W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	966453
Ingress protection:	IP20
Impact resistance:	IK06
Nominal power [W]:	48
Luminous flux [lm]*:	7500
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	C
Material of the body:	aluminium
Colour of the body:	grey

CHARACTERISTICS

LINEA 2 LED is the NEXT GEN pendant and surface-mounted lighting line system, a new generation of lamps dedicated to LED technology. The innovative connection system and pass-through cabling allow the luminaires to be quickly combined into a lighting line. The design used allows for easy assembly and power connection. The aluminium profile body, made from scratch, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. Diodes from a renowned manufacturer integrated in redesigned, completely new modules contribute to a very high luminous efficacy: up to 157 lm/W. This guarantees that the required illuminance level is achieved and significant energy savings are made. The optics are made of UV-resistant PMMA. Thanks to the use of linear lenses, adaptation to different lighting requirements is possible - 3 distribution angles: 90, 60, 45.

APPLICATION

Particularly well suited for indoor use. Dedicated as the primary light source for commercial facilities, manufacturing plants and warehouses. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy-saving LED solutions.


LINEA 2 LED 3360MM 7500LM DALI LS2 7P 840 90D (48W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	966453	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface, suspended
Nominal power [W]:	48	DIMM DALI:	yes
Rated power of the luminaire [W]:	48	Through wiring:	LS2 7P
Supply voltage [V]:	220-240	Net weight [kg]:	4.500
Frequency [Hz]:	50 - 60	Category type:	quick assembly lines
Luminous flux [lm]:	7500	Category of application:	HoReCa, industrial, commercial facilities
Luminous efficacy [lm/W]:	154	LED lifespan L70B50 [h]:	110000
Energy efficiency class:	C	LED lifespan L80B10 [h]:	72000
Electrical protection class:	I	LED lifespan L90B10 [h]:	38000
Colour temperature [K]:	4000	Working temperature [°C]:	from -15 to +35
Color rendering index (Ra) >:	80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	3	Warranty [years]:	5
Beam angle [°]:	90	CE certificate:	170/2023
Optics material:	PMMA	ENEC Certificate:	0334/ENEC/23
Optics:	lens	Manual:	Download PDF
Material of the body:	aluminium	The number of implement units:	1
Colour of the body:	grey	Environmental Product Declaration (EPD):	852/2025
Dimensions (H/W/T/S) [mm]:	47/52/3360	Plik LDT:	Download
Impact resistance:	IK06		

LIGHT CURVES



LINEA 2 LED 3360MM 7500LM DALI LS2 7P 840 90D (48W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
966309	LINEA 2 LED 1680mm - LS2 5P blank module
966316	LINEA 2 LED 1680mm - LS2 7P blank module
966644	LINEA 2 LED 3360mm - LS2 5P blank module
966651	LINEA 2 LED 3360mm - LS2 7P blank module
966323	LINEA 2 LED - closing set
966330	LINEA 2 LED - 840mm cover



LINEA 2 LED - closing set (966323)

Card creation date: 04 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 170/2023