

MODO LED FI 116 370LM 857 IP67 I CL. 30° (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958113
Ingress protection:	IP67
Impact resistance:	IK09
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	370
Colour temperature [K]:	5700
Energy efficiency class:	G
Material of the body:	plastic, steel
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

MODO LED FI 116 370LM 857 IP67 I CL. 30° (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ring material:	Steel
Rated power of the luminaire [W]:	6	Ring colour:	silver
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	ø116/150
Frequency [Hz]:	50 - 60	Mounting dimensions [mm]:	ø102/150
Luminous flux [lm]:	370	Impact resistance:	IK09
Energy efficiency class:	G	Ingress protection:	IP67
Electrical protection class:	I	Net weight [kg]:	0.300
Colour temperature [K]:	5700	Warranty [years]:	2
Beam angle [°]:	30	Index:	958113
Diffuser material:	tempered glass	EAN:	5905963958113
Diffuser type:	transparent	Category type:	accent lighting
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Luminous efficacy [lm/W]:	62
Material of the body:	plastic, steel	Manual:	Download PDF