

TYTAN 2 LED BASIC 1450MM 10300LM 840 IP66 DALI 73W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	909573
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	73
Luminous flux [lm]*:	10300
Colour temperature [K]:	4000
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

TYTAN 2 LED BASIC is a basic line of lighting fixtures which provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy of <150lm/W. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of +/-50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN 2 LED BASIC 1450MM 10300LM 840 IP66 DALI 73W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	909573	Impact resistance:	IK09
EAN:	5905963909573	Ingress protection:	IP66
Light source:	LED module	Mounting version:	surface, suspended
Rated power of the luminaire [W]:	73	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.100
Luminous flux [lm]:	10300	Category type:	battens
Luminous efficacy [lm/W]:	142	AC voltage range [V]:	220 - 240
Energy efficiency class:	C	LED lifespan L70B50 [h]:	103000
Electrical protection class:	I	LED lifespan L80B20 [h]:	65000
Colour temperature [K]:	4000	LED lifespan L90B10 [h]:	32000
Colour rendering index:	80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	≤ 3	Category of application:	industrial, commercial facilities
Power factor:	0.98	Mark D:	yes
Exchangeable source:	yes	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	275/2023
Diffuser type:	matt	ENEC Certificate:	0310/ENEC/23
Material of the body:	PC	PZH certificate:	B-BK-60212-0152/20
Colour of the body:	grey	HACCP:	852/2004
Dimensions (H/W/T/S) [mm]:	1432/85/80	Manual:	Download PDF
Mounting dimensions [mm]:	970	Plik LDT:	Download

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

TYTAN 2 LED BASIC 1450MM 10300LM 840 IP66 DALI 73W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 275/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl