NECTRA LITE 20W 2000LM IP20 SURFACE

DETAILED CARD





TECHNICAL PARAMETERS

502644
IP20
20
2000
4000
>80
Е
PC , steel
white
OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LITE 20W 2000LM IP20 SURFACE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20
Rated power of the luminaire [W]:	20
Luminous flux [Im]:	2000
Luminous efficacy [lm/W]:	100
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	>80
Diffuser type:	OPAL
Material of the body:	PC , steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	88/228/228

Ingress protection:	IP20
Working temperature [°C]:	from -20 to +40
Index:	502644
Category type:	downlights
Category of application:	HoReCa, commercial facilities, educational institutions
Warranty [years]:	5
LED lifespan L70B50 [h]:	30000
LED lifespan L80B20 [h]:	20000
Mounting version:	surface
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Manual:	Download PDF

Card creation date: 23 April 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

