

# NECTRA LITE 25W 2450LM IP20 SURFACE

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	502651
Ingress protection:	IP20
Nominal power [W]:	25
Luminous flux [lm]*:	2450
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	PC , steel
Colour of the body:	white
Diffuser type:	OPAL

## CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

## APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

# NECTRA LITE 25W 2450LM IP20 SURFACE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	25	Working temperature [°C]:	from -20 to +40
Colour temperature [K]:	4000	Index:	502651
Rated power of the luminaire [W]:	25	Category type:	downlights
Luminous flux [lm]:	2450	Category of application:	HoReCa, commercial facilities, educational institutions
Diffuser type:	OPAL	LED lifespan L70B50 [h]:	30000
Luminous efficacy [lm/W]:	98	LED lifespan L80B20 [h]:	20000
Dimensions (H/W/T/S) [mm]:	88/228/228	Mounting version:	surface
Energy efficiency class:	E	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Ingress protection:	IP20	Warranty [years]:	5
Electrical protection class:	II	CE certificate:	<a href="#">344/2023</a>
Colour rendering index:	>80	Manual:	<a href="#">Download PDF</a>
Material of the body:	PC , steel	Plik LDT:	<a href="#">Download</a>
Colour of the body:	white		