NECTRA LITE 25W 2450LM IP20 SURFACE

DETAILED CARD





TECHNICAL PARAMETERS

Index:	502651
Ingress protection:	IP20
Nominal power [W]:	25
Luminous flux [lm]*:	2450
Colour temperature [K]:	4000
Colour rendering index:	80
Energy efficiency class:	Е
Material of the body:	PC + steel
Colour of the body:	white
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LITE 25W 2450LM IP20 SURFACE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	25
Rated power of the luminaire [W]:	25
Luminous flux [lm]:	2450
Luminous efficacy [lm/W]:	98
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	80
Diffuser type:	OPAL
Material of the body:	PC + steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	88/228/228
Ingress protection:	IP20

Working temperature [°C]:	from -20 to +40
Index:	502651
Category type:	downlights
Category of application:	educational institutions, HoReCa, commercial facilities
LED lifespan L70B50 [h]:	30000
LED lifespan L80B20 [h]:	20000
Mounting version:	surface
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	<u>344/2023</u>
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 25 February 2025



