



TECHNICAL PARAMETERS

Index:	950124.
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	13
Luminous flux [lm]*:	1350
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	A
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

APPLICATION


Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

TECHNICAL PARAMETERS TABLE

Index:	950124.	Impact resistance:	IK10
EAN:	5905963950124	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Nominal power [W]:	13	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	16	Corridor function:	yes
Supply voltage [V]:	220-240	Motion sensor:	yes
Luminous flux [lm]:	1350	DIMM DALI:	yes
Luminous efficacy [lm/W]:	83	Dimensions of single box [mm]:	340/340/115
Energy efficiency class:	A	Net weight [kg]:	1.300
Electrical protection class:	I	Gross weight [kg]:	1.480
Colour temperature [K]:	3000	Warranty [years]:	5
Color rendering index (Ra) >:	80	CE certificate:	44/2022
SDCM:	3	Permeability factor of the diffuser:	0.73
Power factor:	0.94	Category type:	bulkheads
Max load (RCR) [W]:	400	Category of application:	educational institutions, HoReCa, commercial facilities
Beam angle [°]:	120	Luminaire rated power P_{min} [W]:	16.10
Diffuser material:	PC	AC voltage range [V]:	220-240
Diffuser type:	OPAL	DC voltage range [V]:	176-276
Diffuser colour:	white	LED lifespan L70B50 [h]:	>54000
Material of the body:	ABS	LED lifespan L80B20 [h]:	>54000
Colour of the body:	white	LED lifespan L90B10 [h]:	>33000
Ring material:	ABS	Light distribution type:	open space
Ring colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	ø340/115	Manual:	Download PDF
Mounting dimensions [mm]:	140	PZH certificate:	B-BK-60212-0619/20

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)