

# 5,90596E+12

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	950124.
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	13
<b>Luminous flux [lm]*:</b>	1350
<b>Colour temperature [K]:</b>	3000
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	A
<b>Material of the body:</b>	ABS
<b>Ring material:</b>	ABS

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	950124.	<b>Impact resistance:</b>	IK10
<b>EAN:</b>	5905963950124	<b>Ingress protection:</b>	IP65
<b>Light source:</b>	LED module	<b>Mounting version:</b>	surface
<b>Nominal power [W]:</b>	13	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Rated power of the luminaire [W]:</b>	16	<b>Corridor function:</b>	yes
<b>Supply voltage [V]:</b>	220-240	<b>Motion sensor:</b>	yes
<b>Luminous flux [lm]:</b>	1350	<b>DIMM DALI:</b>	yes
<b>Luminous efficacy [lm/W]:</b>	83	<b>Dimensions of single box [mm]:</b>	340/340/115
<b>Energy efficiency class:</b>	A	<b>Net weight [kg]:</b>	1.300
<b>Electrical protection class:</b>	I	<b>Gross weight [kg]:</b>	1.480
<b>Colour temperature [K]:</b>	3000	<b>Warranty [years]:</b>	5
<b>Colour rendering index:</b>	>80	<b>CE certificate:</b>	<a href="#">44/2022</a>
<b>SDCM:</b>	≤ 3	<b>Permeability factor of the diffuser:</b>	0.73
<b>Power factor:</b>	0.94	<b>Category type:</b>	bulkheads
<b>Max load (RCR) [W]:</b>	400	<b>Category of application:</b>	HoReCa, commercial facilities, educational institutions
<b>Beam angle [°]:</b>	120	<b>Luminaire rated power <math>O_{min}</math> [W]:</b>	16.10
<b>Diffuser material:</b>	PC	<b>AC voltage range [V]:</b>	220-240
<b>Diffuser type:</b>	OPAL	<b>DC voltage range [V]:</b>	176-276
<b>Diffuser colour:</b>	white	<b>LED lifespan L70B50 [h]:</b>	>54000
<b>Material of the body:</b>	ABS	<b>LED lifespan L80B20 [h]:</b>	>54000
<b>Colour of the body:</b>	white	<b>LED lifespan L90B10 [h]:</b>	>33000
<b>Ring material:</b>	ABS	<b>Light distribution type:</b>	open space
<b>Ring colour:</b>	white	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Dimensions (H/W/T/S) [mm]:</b>	ø340/115	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Mounting dimensions [mm]:</b>	140	<b>PZH certificate:</b>	B-BK-60212-0619/20

# 5,90596E+12

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 04 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 44/2022