

DIONE LED PLUS 1450 LM 840 IP65 OPAL WHITE 13W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	950056.
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	13
Luminous flux [lm]*:	1450
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 1450 LM 840 IP65 OPAL WHITE 13W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	13	Ring colour:	white
Index:	950056.	Dimensions (H/W/T/S) [mm]:	ø340/115
Colour temperature [K]:	4000	Mounting dimensions [mm]:	140
EAN:	5905963950056	Impact resistance:	IK10
Luminous flux [lm]:	1450	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Diffuser type:	OPAL	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	16	Dimensions of single box [mm]:	340/340/115
Supply voltage [V]:	220-240	Net weight [kg]:	1.120
Frequency [Hz]:	50 - 60	Gross weight [kg]:	1.300
Luminous efficacy [lm/W]:	90	Warranty [years]:	5
Energy efficiency class:	E	CE certificate:	44/2022
Electrical protection class:	I	Permeability factor of the diffuser:	0.73
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 3	Category of application:	HoReCa, commercial facilities, educational institutions
Power factor:	0.94	Luminaire rated power P_{min} [W]:	16.10
Beam angle [°]:	120	AC voltage range [V]:	220 - 240
Diffuser material:	PC	DC voltage range [V]:	160 - 256
Diffuser colour:	white	LED lifespan L70B50 [h]:	54000
Material of the body:	ABS	LED lifespan L80B20 [h]:	54000
Colour of the body:	white	LED lifespan L90B10 [h]:	33000
Ring material:	ABS	Light distribution type:	open space
		Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Warranty [years]:	5
		Manual:	Download PDF
		PZH certificate:	B-BK-60212-0619/20

DIONE LED PLUS 1450 LM 840 IP65 OPAL WHITE 13W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 04 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 44/2022